





Brenham 979-836-4591
Bryan 979-778-0325
Navasota 936-825-7577
Sealy 979-885-6140

wctractor.com

Updated 8/11/11 (SUBJECT TO CURRENT ON HAND PRICING)

TOP HAT Gooseneck Trailers

| Order # | Model | Description | List Price | Sale Price |
|---|-------------------|---|------------|------------|
|  | | Lowboy Gooseneck Trailers | | |
| TH-21 | 20 GN-LH 10K | 6'11" X 20' Gooseneck Load Hauler Trailer; Overwide; 2 5/16" Adj. Coupler; 2 - 5,200 lb Axles; Electric Brakes on 1; New 235/16 Radial Tires Load Range E; Spare Rack; Big Pipe; 8" Channel Neck; Diamond Plate Fenders; 4 ft. Slide in Ramps; 10,000 lb. Drop Leg Jack; Chain Tray; Break Away Kit; Treated Floor; 10,000 lb. GVWR | \$4,993.75 | \$3,995.00 |
| TH-63 | ST235 - 16 (6) | 6 Hole Radial Spare; for Top Hat 5, 200 lb. Axle Radial LOAD RANGE E | | \$185.00 |
| TH-22 | 22 GN-HH 12.5K | 6'11" X 22' Gooseneck Heavy Hauler Trailer; Overwide; 2 5/16" Adj. Coupler; 2 - 6,000 lb Axles; Electric Brakes on 2; New 235/16 Radial Tires Load Range E; Spare Rack; 3" Square Tubing; 8" Channel Neck; 5 ft. Slide in Ramps; 10,000 lb. Drop Leg Jack; Chain Tray; Break Away Kit; Diamond Plate Fenders; Safety Chains; Treated Floor; 12,500 lb. GVWR | \$5,618.75 | \$4,495.00 |
| TH-23 | 24 GN-HH 14K | 6'11" X 24' Gooseneck Heavy Hauler Trailer; Overwide; 2 5/16" Adj. Coupler; 2 - 7,000 lb Axles; Electric Brakes on 2; New 235/16 Radial Tires Load Range E; Spare Rack; 3" Square Tubing; 8" Channel Neck; 5 ft. Slide In Ramps; 10,000 lb. Drop Leg Jack; Chain Tray; Break Away Kit; Diamond Plate Fenders; Safety Chains; Treated Floor; 14,000 lb. GVWR | \$6,118.75 | \$4,895.00 |
| TH-65 | P235-16 | 8 Hole Radial Spare; for Top Hat 7,000 lb. Axle Radial LOAD RANGE E | | \$185.00 |
|  | | 14K - 2 AXLE EQUIPMENT HAULER GOOSENECKS | | |
| Standard Equipment: Coupler: 2 5/16" Round Adjustable Jack: Dual 10000# Drop Leg Floor: 2" Treated Pine Stake Pockets & Rubrail Spare Tire & Rack Chain Tray DOT Reflective Tape Driver & Curb Side Steps w/Grab Handles Dovetail w/Fold Over Spring Assist Ramps | | Frame: 12"x14# I-Beam Neck: 8" Channel Crossmembers: 3" Formed Channel 24" OC Side Rails: 5x3x1/4 w/ 3/8x2 Rubrail Frame to Crossmember Struts Bridge Support Truss Anti Flex Torque on 32' or longer Deck Height: 36" | | |
| TH-26A | 20+5 GN-SA 14K | 20' + 5' Dovetail Flatbed Gooseneck; Chain Tray; 2 - 7,000 lb Spring Axles with Electric Brakes on Both; 235/16 Radial Tires On Single Wheels Load Range E; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Drop Leg Jacks; Curb Side Step; Spare; 14,000 GVWR | \$6,868.75 | \$5,495.00 |

| | | | | |
|---|-------------------|---|------------|------------|
| TH-26 | 24+5 GN-SA 14K | 24' + 5' Dovetail Flatbed Gooseneck; Chain Tray; 2 - 7,000 lb Spring Axles with Electric Brakes on Both; 235/16 Radial Tires On Single Wheels Load Range E; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Drop Leg Jacks; Curb Side Step; Spare; 14,000 GVWR | \$7,493.75 | \$5,995.00 |
|  <p style="text-align: center;">w/ 3 axles</p> | | 18K - 3 AXLE EQUIPMENT HAULER GOOSENECKS | | |
| Standard Equipment: Coupler: 2 5/16" Round Adjustable Jack: Dual 10000# Drop Leg Floor: 2" Treated Pine Brake: Electric All Wheel w/BAU. Stake Pockets & Rubrail Spare Tire & Rack Chain Tray DOT Reflective Tape Driver & Curb Side Steps w/Grab Handles Dovetail w/Fold Over Spring Assist Ramps | | Frame Structure: Frame: 12"x16# I-Beam Neck:12"x16# I-Beam Crossmembers: 3" Formed Channel 24" OC Side Rails: 5x3x1/4 w/ 3/8x2 Rubrail Frame to Crossmember Struts Bridge Support Truss Anti Flex Torque on 32' or longer Deck Height: 36" | | |
| TH- | 25+5 GN-SA 18K | 25' + 5' Dovetail Flatbed Gooseneck; Chain Tray; 3 - 7,000 lb Spring Axles with Electric Brakes on Three; 235/16 Radial Tires On Single Wheels Load Range E; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Drop Leg Jacks; Curb Side Step; Spare; 18,000 GVWR | \$8,368.75 | \$6,695.00 |
|  | | 20K DUAL TANDEM FLATBED GOOSENECKS | | |
| Standard Equipment: Coupler: 2 5/16" Round Adjustable Jack: Dual 10000# Drop Leg Floor: 2" Treated Pine Stake Pockets & Rubrail Spare Tire & Rack Chain Tray DOT Reflective Tape Driver & Curb Side Steps w/Grab Handles Dovetail w/Fold Over Spring Assist Ramps | | Frame Structure: Frame: 12"x14# I-Beam Neck: 12"x14# I-Beam Crossmembers: 3" Formed Channel 24" OC Side Rails: 5x3x1/4 w/ 3/8x2 Rubrail Frame to Crossmember Struts Bridge Support Truss Deck Height: 36" | | |
| TH- | 20+5 GN 20K | 20 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 2 5/16" Round Adjustable Coupler; Driver and Curb Side Steps; Chain Tray; 2 Dual Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -14 lb. Per Ft. Beams; 20,000 GVWR | \$9,118.75 | \$7,295.00 |
| TH- | 24+5 GN 20K | 24 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 2 5/16" Round Adjustable Coupler; Driver and Curb Side Steps; Chain Tray; 2 Dual Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -14 lb. Per Ft. Beams; 20,000 GVWR | \$9,118.75 | \$7,695.00 |



22.5K DUAL TANDEM FLATBED GOOSENECKS

Standard Equipment:

Coupler: 2 5/16" Square Load Leveler
 Jack: Dual 10000# Drop Leg
 Floor: 2" Treated Pine
 Stake Pockets & Rubrail
 Spare Tire & Rack
 Lockable Toolbox Between Risers
 DOT Reflective Tape
 Driver & Curb Side Steps w/Grab Handles
 Dovetail w/Fold Over Spring Assist Ramps

Frame Structure:

Frame: 12"x16# I-Beam thru 32'. 19# over 32'
 Neck: 12"x16# I-Beam
 Crossmembers: 3" Formed Channel 16" OC
 Side Rails: 6" Channel w/ 3/8x2 Rubrail
 Frame to Crossmember Gussets
 Bridge Support Truss
 Anti Flex Torque on 32' or longer
 Deck Height: 36"

| | | | | |
|-------|--|---|-------------|-------------|
| TH-31 | 20+5 GN 22.5K | 20 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Driver Side Step; Chain Tray; 2 - 10,000 lb. Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -19 lb. Per Ft. Beams; 22,500 GVWR | \$9,618.75 | \$7,695.00 |
| TH-27 | 25+5 GN 22.5K | 25 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Driver Side Step; Chain Tray; 2 - 10,000 lb. Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -16 lb. Per Ft. Beams; 22,500 GVWR SPECIAL STOCK # N23247 \$7,795.00 | \$10,118.75 | \$8,095.00 |
| TH-28 | 27+5 GN 22.5K | 27 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver Side Step; Chain Tray; 2 - 10,000 lb. Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -19 lb. Per Ft. Beams; 22,500 GVWR | \$11,243.75 | \$8,995.00 |
| TH- | 30+5 GN 22.5K | 27 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver Side Step; Chain Tray; 2 - 10,000 lb. Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -19 lb. Per Ft. Beams; 22,500 GVWR | \$11,868.75 | \$9,495.00 |
| TH- | 35+5 GN 22.5K | 35 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; Spread axles; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver Side Step; Chain Tray; 2 - 10,000 lb. HD Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire; Treated Floor; 2 -Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -19 lb. Per Ft. Beams; 22,500 GVWR | \$12,743.75 | \$10,195.00 |
| TH- | 35+5 GN 22.5K POP UP Dovetail | 35 ft. plus 5 ft. Dovetail Flatbed Gooseneck; POP UP DOVETAIL ; 102" Wide; Spread axles; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver Side Step; Chain Tray; 2 - 10,000 lb. HD Tandems with Brakes; 235/16 Radial Tires On Dual Wheels Load Range E; Spare Tire; Treated Floor; 3 -Spring Assist Flip Over Ramps; Dual 10,000 lb. Jacks; 12 Inch -19 lb. Per Ft. Beams; 22,500 GVWR | \$13,118.75 | \$10,495.00 |



25.9K DUAL TANDEM FLATBED GOOSENECKS

Standard Equipment:
 Coupler: 2 5/16" Square Load Leveler
 Jack: Dual 2-Speed
 Floor: 2" Treated Pine
 Stake Pockets & Rubrail
 Spare Tire & Rack
 Lockable Toolbox Between Risers
 DOT Reflective Tape
 Driver & Curb Side Steps w/Grab Handles
 Low Profile
 HD Dozer Dovetail w/Fold Over Spring Assist Ramps

Frame Structure:
 Frame: 12"x19# I-Beam
 Neck: 12"x19# I-Beam
 Crossmembers:
 3" Formed Channel 16" OC Thru Frame
 Each 4th Crossmember 4" Channel
 Side Rails: 8" Channel w/ 3/8x2 Rubrail
 Frame to Crossmember Gussets
 Bridge Support Truss
 Anti Flex Torque
 Deck Height: 34.5"

| | | | | |
|-----|--|--|-------------|--------------------|
| TH- | 20+5 GN 25.9K Low Profile | 20 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver and Curb Side Step; Chain Tray; 2 - 12,000 lb. Oil Bath Tandems with Brakes; ST235/80R/16 Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; 2 Speed Dual Jacks; D-Rings; 12 Inch -19 lb. Per Ft. Beams; Low Profile Pierced Frame; 25,900 GVWR | \$12,493.75 | \$9,995.00 |
| TH- | 25+5 GN 25.9K Low Profile | 25 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver and Curb Side Step; Chain Tray; 2 - 12,000 lb. Oil Bath Tandems with Brakes; ST235/80R/16 Radial Tires Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; 2 Speed Dual Jacks; D-Rings; 12 Inch -19 lb. Per Ft. Beams; Low Profile Pierced Frame; 25,900 GVWR | \$13,368.75 | \$10,695.00 |
| TH- | 27+5 GN 25.9K Low Profile | 27 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver and Curb Side Step; Chain Tray; 2 - 12,000 lb. Oil Bath Tandems with Brakes; ST235/80R/16 Radial Tires Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; 2 Speed Dual Jacks; D-Rings; 12 Inch -19 lb. Per Ft. Beams; Low Profile Pierced Frame; 25,900 GVWR | \$13,743.75 | \$10,995.00 |
| TH- | 30+5 GN 25.9K Low Profile | 30 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver and Curb Side Step; Chain Tray; 2 - 12,000 lb. Oil Bath Tandems with Brakes ST235/80R/16 Radial Tires Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; 2 Speed Dual Jacks; D-Rings; 12 Inch -19 lb. Per Ft. Beams; Low Profile Pierced Frame; 25,900 GVWR | \$14,368.75 | \$11,495.00 |
| TH- | 35+5 GN 25.9K Low Profile | 35 ft. plus 5 ft. Dovetail Flatbed Gooseneck; 102" Wide; 25K Load Leveler Coupler; Anti-Flex Torque Tube; Driver and Curb Side Step; Chain Tray; 2 - 12,000 lb. Oil Bath Tandems with Brakes; ST235/80R/16 Radial Tires Radial Tires On Dual Wheels Load Range E; Spare Tire & Wheel; Treated Floor; Spring Assist Flip Over Ramps; 2 Speed Dual Jacks; D-Rings; 12 Inch -19 lb. Per Ft. Beams; Low Profile Pierced Frame; 25,900 GVWR | \$14,993.75 | \$11,995.00 |

MORE OPTIONAL TRAILER ACCESSORIES

| | | |
|-----|--------------------------------|--|
| TH- | Air Brakes on 25.9K | Air Brakes with ABS in lieu of electric brakes on the 25.9K |
| TH- | Electric Over Hydraulic | Electric Over Hydraulic in lieu of electric brakes |
| TH- | Electric Over Hydraulic | Electric Over Hydraulic in lieu of electric brakes – w/ disc brakes |
| TH- | Hutch Suspension | Hutch Suspension for 25.9k trailers |
| TH- | HD Dozer Dovetail | Available with 19# Beam only |
| TH- | Combo Dovetail | Pop Up Metal Plate Center section to level rear of dovetail |
| TH- | 3rd Ramp | 3rd ramp for center section with spring assist |
| TH- | 2 Speed Jacks | Dual 2 Speed jacks |
| TH- | D-rings | HD D-rings each |